

TIPC500B-E24



FEATURES

- Certified CB 62368-1 & CB 60950-1
- Meet 80 Plus Bronze
- ATX plus one extra 24Vdc outputs
- Design for 5,000 Meter above sea level
- High Reliability
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

SAFETY STANDARD APPROVAL



DESCRIPTION

TIPC500B-E24 is an industrial level of switching power supply. The power supply comes to offer the total power capacity up to 500W, and provides one extra 24Vdc output, which makes it to be perfectly used for IPC system with motor or printer environment. In addition, the power supply is ideally the best choice for ATM, POS, KIOSK or any other system with printer applications to use. The product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.

GENERAL SPECIFICATIONS

Dimension (L x W x H):	140 x 150 x 86 (mm) 5.51 x 5.91 x 3.39 (inch)	Environment	
Efficiency:	80 Plus Bronze	Working temperature:	0°C to 50°C
Hold-up time:	115V / 60Hz: ≥ 16ms 230V / 50Hz: ≥ 16ms	Storage temperature:	-20°C to + 80°C
Operating altitude:	5,000 meters above sea level	Working humidity:	85% RH non-condensing
		Storage humidity:	95% RH non-condensing
		MTBF:	100,000 hours of continuous operation at 25°C, Max.-output load
		Applications:	ATM, POS, KIOSK System

INPUT SPECIFICATIONS

Input voltage:	90-264Vac
Input frequency:	47-63Hz
Input current:	115Vac @ 6A, 230Vac @ 3A

OUTPUT RATING

Outputs	+3.3V	+5V	+12V1	+12V2	+24V	-12V	+5Vsb	-5V*
Max.	18.0A	18.0A	18.0A	18.0A	8.0A	0.5A	3.0A	0.1A
Min.	0.1A	0.1A	0.5A	0.5A	0.0A	0.0A	0.0A	0.0A
Regulation	±5%	±5%	±5%	±5%	±10%	±10%	±5%	±10%
Ripple/Noise	50 mV	50 mV	120 mV	120 mV	120 mV	120 mV	50 mV	100 mV

The +3.3V and +5V total output shall not exceed 100W

*-5V output is optional

MECHANICAL SPECIFICATIONS

UNIT: mm [inch]

